




























# ambiente

TECHNICAL SHEET									
ARTICLE ARTICOLO	TULLE FR 0199				COLLECTION COLLEZIONE <b>firewall</b> ®				
COMPOSITION COMPOSIZIONE	100 % POLYESTER FR								
WIDTH / CM ALTEZZA	290/300								
HEM ORLO	SELVEDGE	LEAD BAND							
WEIGHT GR / M2 PESO GR / M2	48								
DESIGN REPEAT RAPPORTO DISEGNO	NO								
FINISHING FINISSAGGIO	YARN DYED								
HARMONIZED CUSTOM TARIFF TARIFFA DOGANALE	54075300								
LIGHT FASTNESS SOLIDITA' ALLA LUCE		1	2	3	4	5	6	7	8
DIMENSIONAL STABILITY STABILITA' DIMENSIONALE	WARP ORDITO	0-1%	1%-2%	2%-3%	3%-4%	4%-5%	OVER		
	WEFT TRAMA	0-1%	1%-2%	2%-3%	3%-4%	4%-5%	OVER		
FASTNESS COLOR TO RUBBING RESISTENZA ALLO SFREGAMENTO	wet umido	1	2	3	4	5	6	7	8
	dry secco	1	2	3	4	5	6	7	8
MARTINDALE TEST ABRASIONE	10000	15000	20000	30000	35000	40000	50000	OVER	
PILLING	1	2	3	4	5				
FR TEST OMOLOGAZIONI	ITALIA CLASSE 1	FRANCE M1	GERMANY B1	BRITISH BS TYPE B	NFPA 701	EN 13773	IMO		
END USE UTILIZZO									
PACKING IMBALLAGGIO	FWR	DFR	Legenda : FWR=FULL WIDTH ROLL / DFR=DOUBLE FOLDED ROLL						
CARE SYMBOLS							wash lavaggio		
							iron stiro		
							cleaning dry lavaggio a secco		
OTHER SYMBOLS ALTRI SIMBOLI									
REACH	conformity and information according to REACH								



